



Product Image	
Part number	909020116 – PAC OneProx™ GS3 LF Vandal Reader - yellow and black 909022116 – PAC OneProx™ GS3 LF Vandal Reader - blue and grey
Dimensions	W 100 x H 100 x D 16mm
Weight	410g
RFid Frequency	Low Frequency (125kHz and 153.6kHz)
PAC ID Devices	PAC, Stanley, KeyPAC, Wiegand
Programmable Output Formats	PAC, PAC64 and Wiegand
Maximum Read Range	40mm
Intruder Grading	Security Grade 3
Environment	IP65 - Indoor/ Outdoor weather resistant
Power	12 – 24V DC, <100mA @ 12V DC
Operating Temperature	-40 to 66 oC
Operating Humidity	10 to 85% Relative Humidity
Audio/Visual Indicators	Audible Sounder and Red/Green LEDs
Tamper Output	Yes, certified to EN 50131-1 and EN 50131-3
Recommended Cabling	PAC output - 6 core 24 AWG alarm cable (unscreened) Wiegand output – 5 core 22 AWG cable
Material	Stainless Steel & Polycarbonate
Certification	CE compliant



Date of print/release: (September 2020)

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDx and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
 Bredbury, Stockport, Cheshire, SK6 2SZ
 customerservices@pacgdx.com | +44 (0) 161 406 3400
 www.pacgdx.com